



## **SPECIFICATIONS**

Waveform:	Biphasic Truncated Exponential (BTE) waveform
	(Impedance compensation)
Energy:	Adult: 185 to 200J (±5%)
	Paediatric: 45 to 50J (±5%)
Operating Mode:	Semi-Auto
Charge Time:	Less than 12 seconds
Analysis Time:	8-13 seconds
Shock Time:	Delivers 200 shocks with full battery
ECG	
Lead:	II (RA, LL)
Patient Impedance:	25 to 175ohm
Detection V/F	more than 200μV
V/T	more than 160 per min
CONTROLS Standard:	Open (power) switch, shock button,
Standard:	Open (power) switch, shock button,
	Adult/Paediatric mode switch
INDICATORS	
Visible:	ICON Indicator, Status LCD (unit status, battery
	status, temperature status),
	LED (Adult/Paediatric mode switch LED)
Audible:	Speaker (voice prompt), Beep (CPR indication)
PHYSICAL	
Dimensions:	294H x 240W x 95mmD
	Approx. 2.65kg (including battery,
Weight:	Approx. 2.65kg (including battery, excluding pads)
Weight:	
Weight: SELF TEST	excluding pads)
Weight:	excluding pads)  Every 24 hours, 1 week, 1 month
Weight: SELF TEST	excluding pads)

Status LCD displays 'O' / 'X'

#### DATA BACKUP AND COMMUNICATION

Standard SD card, IR communication port

ADULT/PAEDIATE	RIC PADS
Standby Life:	2 years from date of manufacture
Electrodes:	Disposable pads
Placement:	Adult: Anterior-lateral
	Paediatric: Anterior-posterior
Minimum active g	el area: 80cm2 +/-5%
Cable Length:	Approx. 1.8m
Environmental Co	onditions
Temperature:	Operation: 0 to 43°C (32 to 109.4°F)
	Storage: 0 to 43°C (32 to 109.4°F)

Temperature:	Operation: 0 to 43°C (32 to 109.4°F)	
	Storage: 0 to 43°C (32 to 109.4°F)	
Relative Humidity:	5 to 95% RH (non-condensing)	

### **BATTERY**

Туре:	LiMnO2, disposable, long-life primary cell
Voltage/Capacity:	15V, 4200 mAh
Shelf Life:	2 years from date of manufacture
	(in the original packaging)
Standby Life:	5 years from date of manufacture
	(inserted in the AED)
Discharge:	A minimum of 200 shocks
	(except the CPR period between the
	defibrillation therapy) or 10 hours of
	operating time at 20°C

#### **Environmental Conditions**

Temperature:	Operation: 0 to 43°C (32 to 109.4°F)	
	Storage: 0 to 43°C (32 to 109.4°F)	
Relative Humidity:	5 to 95% RH (non-condensing)	

# www.medianadefib.co.uk

t. +44 (0) 08456 448808

Test Result:

- e. sales@reliancemedical.co.uk
- w. www.medianadefib.co.uk



